



OPTIMIC™ 2140

Ruggedized Fiber Optic Microphone for Remote Monitoring Applications

Stand-alone, ruggedized fiber optic microphone for indoor and outdoor acoustic monitoring applications. Ideal for industrial use, placement in heavy machinery, or where the microphone requires very robust housing and fiber cables.

FEATURES

- ▶ Robust design suited to industrial applications
- ▶ Absolute EMI/RFI immunity
- ▶ Completely passive sensor with no metal or electrical parts
- ▶ Excellent sound accuracy
- ▶ Standard analog output
- ▶ High reliability and environmental stability
- ▶ Optical fiber connection over extended lengths without signal loss
- ▶ Exceptionally low sensitivity to vibration
- ▶ Plug-and-play system
- ▶ Cost-effective, long-term solution

TECHNICAL SPECIFICATIONS

Polar Pattern	Omnidirectional
Frequency Response	30-8,000 Hz
Conformity 30 - 1,000 Hz	±0.5 dB
Conformity 1,000 - 8,000 Hz	±4.0 dB
Sensitivity	100 mV/Pa ±10% at 1 kHz
Equivalent Self-Noise	≤31 dBA
Maximum Acoustic Pressure	114 dB SPL
Total Harmonic Distortion	<1% at 84 dB SPL
Equivalent Vibration Sensitivity	Max. 45 dB SPL/g at 1 kHz
Supply Voltage	8-15 V DC
Current Drain (max.)	80 mA
Operating Temperature	-20 to +60 °C (-4 to +140 °F)
Storage Temperature	-20 to +60 °C (-4 to +140 °F)
Humidity - 1000 hours	Up to 95% RH at 40 °C
MTBF	>100,000 hours
Microphone Head	
Material	Delrin
Dimensions D/L	10/70 mm
Weight	5 g
Optical Cable Length	10 m

APPLICATIONS

- ▶ Industrial equipment monitoring
- ▶ High voltage electrical utilities
- ▶ Oil and gas detection sites
- ▶ Highly explosive areas
- ▶ High RF areas
- ▶ Severe electromagnetic fields
- ▶ Aerospace measurements
- ▶ Petrochemical facilities
- ▶ EMC test labs



OPTIMIC™ 2140 System Kit

Complete, versatile, cost-effective solution


Optoacoustics' OPTIMIC 2140 system is comprised of our advanced OPTIMIC fiber optic microphone, electro-optic unit, audio cable with BNC connector, DC power supply and a ruggedized carrying case.




Optoacoustics EOU 100 electro-optic unit showing fiber optic, audio, and power supply connections

PRODUCT ORDERING GUIDE

Use the matrix below to select options and accessories for your order.



Options	Fiber Optic Cable Type	Electro-Optic Unit Type	
Item	Black Polyamide Ø 5.1 mm	EOU 100 Single Channel	EOU 200 Single Channel
Code	R	A	B
			

Accessories	Extension Cable Type (Specify length from 10-100 m)			
Item	Outdoor, Milspec Ø 5 mm	Outdoor, Polyamide Ø 5.1 mm	Indoor, Rugged Ø 3.0 mm	Indoor, Zip Cord Ø 3.0 x 2 mm
Code	1	2	3	4
				



SOUND SOLUTIONS FROM LIGHT TECHNOLOGY

Optoacoustics is a leading manufacturer of high performance, optical fiber-based sound and vibration sensors. Each of our products combines the natural intelligence of optics and acoustics to meet technical performance demands which cannot be addressed by conventional sensing solutions. Optoacoustics' pioneering technology is protected by over 20 international patents.

HEADQUARTERS
17 Hata'asia Street
60212 Or-Yehuda
Israel

TOLL-FREE +1 866-867-5029
PHONE +972 3-634-4488
FAX +972 3-634-9292
EMAIL info@optoacoustics.com

Copyright © 2007 Optoacoustics Ltd. All rights reserved. The information appearing here is subject to change without notice. Unless otherwise indicated, all product names are trademarks of Optoacoustics Ltd.

DS-2140-1 1009